Application No.: 09/675,778
Filed: September 29, 2000
Attorney Docket No.: 801939-000101
Attorney: Peter J. Prommer
Telephone No.: (312) 425-3900

REPLACEMENT SHEET

FIG. 1



FIG. 2



Application No.: 09/675,778
Filed: September 29, 2000
Attorney Docket No.: 801939-000101
Attorney: Peter J. Prommer
Telephone No.: (312) 425-3900

FIG. 3



FIG. 4


PDE Specification/ht
Equation: p· C· T' -V· (kVT) =Q + h(Text· T)+ Ctrans · (T4ambtrans ·T4). T = temperature
Subdomain selection
1
Name
1
Active in the subdomain
PDE coefficients
Unlock
Coefficient
Value
Description
p
8930
Density
C
340
Heat capacity
k
384
Coeff. of heat conduction
Q
1./(0*(1+alpha*(T-T0)))*I
Heat source
h trans
0
Convect. heat transf. coeff.
Text
0
External temperature
Ctrans
0
User defined constant
Tambtrans
0
Ambient temperature
On top
OK
Cancel
Apply
60
62
62a
66
64
64a
64a

Application No.: 09/675,778
Filed: September 29, 2000
Attorney Docket No.: 801939-000101
Attorney: Peter J. Prommer
Telephone No.: (312) 425-3900

REPLACEMENT SHEET

FIG. 5



FIG. 6


Boundary Conditions/Coefficient View
Equation: n·(cVu+αu-γ) + q·u = g·h^T λ ; h·u = r
q
g
h
r
q coefficient
u
v
T
1
0
0
0
0
ps
0
1
0
ps
0
0
0
ht
Boundary selection
1
2
3
4
Name:
On top
OK
Cancel
Apply
80
82a
82b
82c
82d
84a
84b
84c
84d
88
90
92a
92b
92c
94
96

Application No.: 09/675,778
Filed: September 29, 2000
Attorney Docket No.: 801939-000101
Attorney: Peter J. Prommer
Telephone No.: (312) 425-3900

REPLACEMENT SHEET

FIG. 6A



Application No.: 09/675,778
Filed: September 29, 2000
Attorney Docket No.: 801939-000101
Attorney: Peter J. Prommer
Telephone No.: (312) 425-3900

REPLACEMENT SHEET

FIG. 7



Application No.: 09/675,778
Filed: September 29, 2000
Attorney Docket No.: 801939-000101
Attorney: Peter J. Prommer
Telephone No.: (312) 425-3900

REPLACEMENT SHEET

FIG. 8

140

$$\begin{cases} d_{a\,lk}\dfrac{\partial u_k}{\partial t} - \dfrac{\partial}{\partial x_j}\left(c_{lkji}\dfrac{\partial u_k}{\partial x_i} + \alpha_{lkj}u_k - \gamma_{lj}\right) + \beta_{lki}\dfrac{\partial u_k}{\partial x_i} + a_{lk}u_k = f_l & \Omega \quad 142 \\ n_j\left(c_{lkji}\dfrac{\partial u_k}{\partial x_i} + \alpha_{lkj}u_k - \gamma_{lj}\right) + q_{lk}u_k = g_l - h_{ml}\lambda_m \,| & \partial\Omega \quad 146a \\ h_{ml}u_l = r_m & \partial\Omega \quad 146b \end{cases}$$

146

FIG. 9

150

$$\begin{cases} d_{a\,lk}\dfrac{\partial u_k}{\partial t} + \dfrac{\partial \Gamma_{lj}}{\partial x_j} = F_l & \Omega \quad 152 \\ -n_j\Gamma_{lj} = G_l + \dfrac{\partial R_m}{\partial u_l}\lambda_m & \partial\Omega \quad 154a \\ 0 = R_m & \partial\Omega \quad 154b \end{cases}$$

154

Application No.: 09/675,778
Filed: September 29, 2000
Attorney Docket No.: 801939-000101
Attorney: Peter J. Prommer
Telephone No.: (312) 425-3900

FIG. 10

$$324\ \left\{\begin{array}{ll}
\gamma_{lj} = \Gamma_{lj} & f_l = F_l \\[2ex]
c_{lkji} = -\dfrac{\partial \Gamma_{lj}}{\partial\left(\dfrac{\partial u_k}{\partial x_i}\right)} & \alpha_{lkj} = -\dfrac{\partial \Gamma_{lj}}{\partial u_k} \\[4ex]
\beta_{lki} - \dfrac{\partial F_l}{\partial\left(\dfrac{\partial u_k}{\partial x_i}\right)} & a_{lk} = -\dfrac{\partial F_l}{\partial u_k} \\[4ex]
g_l = G_l & r_l = R_l \\[2ex]
q_{lk} = -\dfrac{\partial G_l}{\partial u_k} & h_{lk} = -\dfrac{\partial R_l}{\partial u_k}
\end{array}\right.$$

FIG. 11

$$240\ \left\{\begin{array}{l}
\Gamma_{lj} = c_{lkji} \dfrac{\partial u_k}{\partial x_l} \alpha_{lkj} u_k + \gamma_{lj} \\[2ex]
F_l = f_l - \beta_{lki}\, a_{lk} u_k \\[1ex]
G_l = g_l - q_{lk} u_k \\[1ex]
R_m = r_m - h_{ml} u_l
\end{array}\right.$$

FIG. 12

300

$$\begin{cases} \int_{\Omega}\left(\left(c_{lkji}\frac{\partial u_k}{\partial x_i} + \alpha_{lkj}u_k\right)\frac{\partial v}{\partial x_j} + \left(d_{a\,lk}\frac{\partial u_k}{\partial t} + \beta_{lki}\frac{\partial u_k}{\partial x_i} + a_{lk}u_k\right)v\right) dx + \\ \int_{\partial\Omega} q_{lk}u_k\, vds = \int_{\Omega}\left(\gamma_{lj}\frac{\partial v}{\partial x_j} + f_l v\right) dx + \int_{\partial\Omega}(g_l - h_{ml}\lambda_m)\, v\, ds \\ \int_{\partial\Omega} \mu h_{mk}u_k\, ds = \int_{\partial\Omega} \mu r_m\, ds \end{cases}$$

FIG. 13

302

$$\begin{cases} \int_{\Omega}\left(\Gamma_{lj}\frac{\partial v}{\partial x_j} + F_l v - d_{a_{lk}}\frac{\partial u_k}{\partial t} v\right) dx + \int_{\partial\Omega}\left(G_l + \frac{\partial R_m}{\partial u_l}\lambda_m\right) vds = 0 \\ \int_{\partial\Omega} R_m \mu\, ds = 0 \end{cases}$$

FIG. 14

304

$$\begin{cases} U_k(x) = \sum_{l=1}^{N_p} U_{l,k}\phi_l(x), \quad \Lambda_m(x) = \sum_{K=1}^{N}\sum_{L=1}^{n} \Lambda_{K,L,m}\Psi_{K,L}(x) \end{cases}$$

FIG. 15

306

$$\begin{cases} \int_\tau \left(c_{lk\,ji}\, U_{I,k} \frac{\partial \phi_I}{\partial x i} + \alpha_{lkj} U_{l\,k} \phi_l \right) \frac{\partial \phi J}{\partial x_j} dx + \\ \int_\tau \left(d_{a\,lk} \frac{\partial U_{I,k}}{\partial I} \phi_i + \beta_{lkj} U_{i,k} \frac{\partial \phi I}{\partial x_I} + \alpha_{lk} U_{i,k} \phi_i \right) \phi_J dx + \\ \int_{\partial\tau} q_{lk}\, U_{l,k}\, \phi_I\, \phi_J\, ds = \int_\tau \left(\gamma_{Ij} \frac{\partial \phi J}{\partial x_j} + f_I \phi_J \right) dx + \\ \int_{\partial\tau} (g_I - h_{mI} \Lambda_{K,L,m} \Psi_{K,L}) \phi_J\, ds \end{cases}$$

FIG. 16

308

$$\left\{ \int_{\partial\tau} h_{mk}\, U_{J,k}\, \phi_I\, \Psi_{K,L}\, ds = \int_{\partial\tau} r_m \Psi_{K,L}\, ds \right.$$

FIG. 17

312

$$\begin{cases} \int_\tau \left(\Gamma_{lj} \frac{\partial \phi_J}{\partial xj} + F_l \phi_J - d_{\alpha lk} \frac{\partial u_k}{\partial I} \phi_J \right) dx + \int_{\partial t} \left(G_I + \frac{\partial R_m}{\partial u_l} \Lambda_{K,L,m} \Psi_{K,L} \right) \phi_J\, ds = 0 \\ \int_{\partial\tau} R_m \Psi_{K,L}\, ds = 0 \end{cases}$$

Application No.: 09/675,778
Filed: September 29, 2000
Attorney Docket No.: 801939-000101
Attorney: Peter J. Prommer
Telephone No.: (312) 425-3900

REPLACEMENT SHEET

FIG. 18

$$
310 \left\{
\begin{aligned}
&DA_{(J,l),(I,k)} = \int_\tau d_{alk} \phi_I \phi_J \, dx \\
&C_{(J,l),(I,k)} = \int_\tau c_{lkji} \frac{\partial \phi_I}{\partial x_i} \; ? \; \frac{\partial \phi_J}{\partial x_j} \, dx \\
&AL_{(J,l),(I,k)} = \int_\tau \alpha_{lkj} \phi_I \; ? \frac{\partial \phi_J}{\partial x_j} \, dx \\
&BE_{(J,l),(I,k)} = \int_\tau \beta_{lki} \frac{\partial \phi_I}{\partial x_i} \phi_j \, dx \\
&A_{(J,l),(I,k)} = \int_\tau a_{lk} \phi_I \phi_J \, dx \\
&Q_{(J,l),(I,k)} = \int_\tau q_{lk} \phi_I \phi_J \, ds \\
&GA_{(J,l)} = \int_\tau \gamma_{lj} \frac{\partial \phi_J}{\partial x_j} \, dx \\
&F_{(J,l)} = \int_\tau f_I \phi_J \, dx \\
&G_{(J,l)} = \int_{\partial \tau} g_I \phi_J \, ds \\
&H_{(K,L,m),(I,k)} = \int_{\partial \tau} h_{mk} \phi_I \Psi_{K,L} \, ds \\
&R_{(K,L,m)} = \int_{\partial \tau} r_m \Psi_{K,L} \, ds
\end{aligned}
\right.
$$

FIG. 19

$$
320 \left\{
\begin{aligned}
&DA \frac{\partial U}{\partial t} + C + AL + BE + A + Q)\, U + H^T \Lambda = GA + F + G \\
&H U = R
\end{aligned}
\right.
$$

REPLACEMENT SHEET

FIG. 20

322
$$\begin{cases} DA\dfrac{\partial U}{\partial t} + H^{T}\Lambda = GA + F + G \\ R = 0 \end{cases}$$

FIG. 21

32
$$\begin{cases} J(U^{(k)})\Delta U^{(k)} = -R(U^{(k)}) \\ U^{(k+1)} = U^{(k)} + \lambda_k \Delta U^{(k)} \end{cases}$$

FIG. 22


200
210
Select first application mode.
212
Done with all application modes?
YES
A
NO
214
Specify the physical properties associated as active with each application mode.
216
Specify boundary conditions for each application mode.
218
Create and initialize data structure using physical properties and boundary conditions for each application mode.
220
Form coefficient partial differential equation and store in temporary data structure accordingly.
222
Form general partial differential equation and store in temporary data structure accordingly.
224
Modify boundary conditions and/or partial differential equations of current application mode.
226
Next application mode.

Application No : 09/675,778
Filed September 29, 2000
Attorney Docket No.: 801939-000101
Attorney Peter J. Prommer
Telephone No.: (312) 425-3900

FIG. 23



FIG. 24


500
The Class Hierarchy of FEMLAB
flbase
Basic GUI functionality
Application modules
flpde
flsme
Geometry dimension
flpdeg(n)
flpdec(n)
fl1d
fl2d
flpdec2d(n)
flpdec1d(n)
Application modules
flpdedc2d
flpdeac
flpdees2d
Applications
flwaveguide

FIG. 25

1-D Physics Application Modes

Application mode	Class name	Parent class
Diffusion	flpdedf1d	flpdedf
Heat Transfer	flpdeht1d	flpdeht

502

1-D PDE Application Modes

Application mode	Class name	Parent class
Coefficient PDE model, n variables	flpdec1d *(n)*	flpdec *(n)*
General PDE model, n variables	flpdeg1d *(n)*	flpdeg *(n)*

504

FIG. 26

2-D Physics Application Modes

Application Mode	Class name	Parent class
AC Power Electromagnetics	flpdeac	flpdec2d
Conductive Media DC	flpdedc2d	flpdedc
Diffusion	flpdedf2d	flpdedf
Electrostatics	flpdees2d	flpdees
Magnetostatics	flpdems2d	flpdems
Heat Transfer	flpdeht2d	flpdeht
Incompressible Navier-Stokes	flpdens2d	flpdens
Structural Mechanics, Plane Stress	flpdeps	flpdec2d
Structural Mechanics, Plane Strain	flpdepn	flpdec2d

506

PDE Application Modes

Application Mode	Class name	Parent class
Coefficient PDE model, n variables	flpdec2d *(n)*	flpdec *(n)*
General PDE model, n variables	flpdeg2d *(n)*	flpdeg *(n)*

508

FIG. 27

Application Object Properties

Property name	Description	Data type
dim	Names of the dependent variables	Cell array of strings
form	PDE form	String (coefficient/ general)
name	Application name	String
parent	Parent class names	String. cell array of strings. or the empty matrix
sdim	Names of the independent variables (space dimensions)	Cell array of stings
submode	Name of current submode	String (std/wave)
tdiff	Time differentiation flag	String (on/off)

514

FIG. 28

512

```
function obj = myapp()
%MYAPP Constructor for a FEMLAB application object.

obj. name = 'My first FEMLAB application';
obj. parent = 'flpdeht2d';


% MYAPP is a subclass of FLPDEHT2D:

p1 = "flpdeht2d;
obj = class (obj, 'myapp' , p1);
set (obj , 'dim' , default_dim (obj));
```

FIG. 29

Physics Modeling Methods

514

Function	Purpose
appspec	Return application specifications.
bnd_compute	Convert application-dependent boundary conditins to generic boundary coefficents.
default_bnd	Default boundary conditions.
default_dim	Default names of dependent variables
default_equ	Default PDE coefficients/Material parameters.
default_init	Default initial conditions.
default_sdim	Default space dimension variables.
default_var	Default application scalar variables.
dim_compute	Return dependent variables for an application.
equ_compute	Convert application-dependent material parameters to generic PDE coefficients.
form_compute	Return PDE form.
init_compute	Convert application-dependent initial conditions to generic initial conditions
posttable	Define assigned variable names and post-processing information.

REPLACEMENT SHEET

FIG. 30



FIG. 31

530 $$\Delta E_Z + (2\pi ik)^2 E_Z = 0$$

532 $$k = \frac{1}{\lambda} = \frac{f}{c}$$

534 $$\overline{n} \cdot (\nabla E_Z) + 2\pi ik_X E_Z = 4\pi ik_X \sin\left(\frac{\pi}{d}(y - y_0)\right)$$

536 $$k^2 = k_x^2 + k_y^2$$

538 $$k_x = \sqrt{\frac{1}{\lambda^2} \quad \frac{1}{(2d)^2}}$$

540 $$n \cdot (\nabla E_Z) + 2\pi ik_X E_Z = 0$$

542 $$E_Z = 0$$

544 $$f_c \ \frac{c}{2d}$$

FIG. 32

550

```
function obj = flwaveguid (varargin)
%FLWAVEGUIDE Constructor for a waveguide application object.

 obj. name = 'In-Plane Waveguide';
 obj. parent = 'flpdeac';

 % FLWAVEGUIDE is a subclass of FLPDEAC:
 p1 = flpdeac;
 obj = class (obj), 'flwaveguide' ,p1);
 set (obj), 'dim' , default_dim(obj));
```

FIG. 33

552

fem.user fields

Field	Description
geomparam	1-by-2 structure of geometry parameters.
entrybnd	Index to the entry boundary
exitbnd	Index to the exit boundary
freqs	Frequency vector

FIG. 34

554

fem.user fields

Field	Description
startpt	Index of the lower left corner point of the waveguide.
type	Type of waveguide. (*straight* or *elbow*)

FIG. 35

556

geomparam fields

Field	Description	Defaults for elbow	Defaults for straight
entrylength	Length of the entrance part of the waveguide.	0.1	0.1
exitlength	Length of the exit part of the waveguide.	0.1	Not used
radius	Outer radius of the waveguide bend.	0.05	Not used
width	Width of the waveguide.	0.025	0.025
cavityflag	Turn resonance cavity *on* or *off*	0	0
cavitywidth	Width of the resonance cavity	0.025	0.025
postwidth	Width of the protruding posts.	0.005	0.005
postdepth	Depth of the protruding posts.	0.005	0.005